

OD-3528-60-12

12V
DC



IP67



Features:

- Super-bright 3528 SMD, minimum 6.7lm per diode
- 12V DC input
- Standard packaging is 16.5ft reel, customizable size available
- 3M adhesive tape in the back for easy mounting
- Universal Color Consistency

Applications:

- Widely used in advertisement and exhibit application
- Ideal for architectural and landscape lighting
- Edge-light transparent or diffused materials
- Highlight path and contour marking



Product Specification

Model Number	OD-3528-60-12
LEDs/m	SMD 3528 x 60pcs
Voltage	12V DC
Power Consumption/ft	≤1.46W
Lumen's Output(lm)/ft	22.57-37.62lm
CRI	≥80, ≥90
Beam Angle	120°
Cuttable	Every 3 LED/50mm(1.97")
Dimmable	Yes
Operating Temperature	-13° to 140° F
Color Available	Red, Yellow, Green, Blue, Purple, Amber, Pink, 2,300K*, 2,400K*, 2,500K*, 2,600K*, 2,700K*, 3,000K, 3,200K*, 3,500K*, 3,800K*, 4,000K, 4,500K*, 5,000K, 5,800K*, 6,500K, 10,000K*, 11,000K*, and 12,000k*

*Also available for special order