

## ID-3528-60-24



### Features:

- Super-bright 3528 SMD, minimum 6.75lm per diode
- 12V DC input
- Standard packaging is 16.5ft reel, customizable size available
- 3M adhesive tape in the back for easy mounting
- Universal Color Consistency

### Applications:

- Widely used in advertisement and exhibit application
- Ideal for architectural and landscape lighting
- Edge-light transparent or diffused materials
- Highlight path and contour marking



### Product Specification

|                       |                                                                                                                                                                                                           |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model Number          | ID-3528-60-24                                                                                                                                                                                             |
| LEDs/m                | SMD 3528 x 60pcs                                                                                                                                                                                          |
| Voltage               | 24V DC                                                                                                                                                                                                    |
| Power Consumption/ft  | ≤1.45W                                                                                                                                                                                                    |
| Lumen's Output(lm)/ft | 73-123lm                                                                                                                                                                                                  |
| CRI                   | ≥80, ≥90                                                                                                                                                                                                  |
| Beam Angle            | 120°                                                                                                                                                                                                      |
| Cutable               | Every 3 LED/100mm(3.94")                                                                                                                                                                                  |
| Dimmable              | Yes                                                                                                                                                                                                       |
| Operating Temperature | -13° to 140° F                                                                                                                                                                                            |
| Color Available       | Red, Yellow, Green, Blue, Purple, Amber, Pink, 2,300K*, 2,400K*, 2,500K*, 2,600K*, 2,700K*, 3,000K, 3,200K*, 3,500K*, 3,800K*, 4,000K, 4,500K*, 5,000K, 5,800K*, 6,500K, 10,000K*, 11,000K*, and 12,000k* |

\*Also available for special order